

Polyurethane Varnish

Formulated from a 'single pack' Alkyd Urethane Resin. Once dry, Polyurethane Varnish provides a clear finish for interior wood surfaces where a hard, durable coating is required. It also has exceptional resistance to alcohol, dilute acid, abrasion and heat. The gloss finish gives a superb mirror like effect.

Particularly suitable for use on internal doors and joinery, kitchen furniture and worktops. Additional coats improve the hardness and finish (2-3 coats).

Preparation: Before use, test a small inconspicuous area with all products to be used, to ensure a satisfactory final finish & compatibility. Product has a light amber hue so is not recommended over painted surfaces.

Ensure surfaces are clean, dry and free from wax, oil and dirt. Sand down to remove stains, previous paints or other coatings.

Application: By brush or roller. Stir product thoroughly before use to ensure that any sediment is fully re-dispersed and stir occasionally during use. Un-dispersed sediment can impact the gloss level. Ideal application temperature between 15-25°C. Low temperature/high humidity adversely affects drying time.

Drying Times: Touch Dry: 2 hours. Hard Dry: 12 hours.

Overcoat Time: 12 hours or overnight.

Full Hardness: Up to 7 days.

Coverage Guide: Up to 14 square metres per litre.

Thinners: White Spirit

HIGH VOC content: 25-50% VOCs (Volatile Organic Compounds) contribute to atmospheric pollution. EU limit value for this product (cat: A/e) : 400g/l (2010). This product contains max 400g/l VOC.

Remove as much of the product as possible from application equipment before washing. Do not empty product into drains or waterways. Some local authorities have special facilities for disposal of waste coatings. To avoid the risk of spillage, always store and transport in secure upright position. During surface preparation, avoid inhalation of dust. Wear a suitable face mask if sanding.

Health, Safety & Environmental Information

WARNING

Contains: HYDROCARBONS, C9-C11,
<2% AROMATICS

Flammable liquid and vapour.

May cause drowsiness or dizziness.

Keep out of reach of children.

If medical advice is needed, have product container or label at hand.

Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Avoid breathing vapours/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Dispose of contents/container in accordance with national regulations.

Repeated exposure may cause skin dryness or cracking.

Contains: 2-BUTANONE OXIME. May produce an allergic reaction.

PAINT UN 1263



Barrettine
TRUSTED BY THE PROFESSIONALS

St. Ivel Way, Warmley, Bristol BS30 8TY.

T +44 (0) 117 960 0060 F +44 (0) 117 935 2437

E sales@barrettine.co.uk www.barrettinePro.co.uk