

Yacht Varnish

A tough, top quality varnish with a high gloss finish. Protects against cracking and flaking caused by UV light. Also provides complete and long-lasting protection under testing weather conditions. Suitable for exterior and interior applications. Ideal for use on boats, doors, window frames, garden furniture and many other items, especially in a marine or exposed environment.

Preparation: Before use, test a small inconspicuous area with all products to be used, to ensure a satisfactory final finish & compatibility. Product has a light amber hue so is not recommended over painted surfaces. Not for use as a waterproof membrane. Ensure surfaces are clean, dry and free from dirt, oil and grease. Rub down thoroughly with fine glasspaper and dust off. Blemishes and cracks or nail holes should be filled with a suitable wood filler then sanded down.

On previously painted timber, sand off previous paints or treatments and then proceed as with new timber.

New timber - thin 5-10% with White Spirit for the first coat. Allow 12 hours before applying the next coat. Further 2-3 coats improve protection and finish. Ensure all end grain or wood is thoroughly treated. Lightly sand between coats with a very fine glasspaper for an optimal finish.

Application: By brush, roller or spray. Stir thoroughly. Ideal application temperature between 15-25°C.

Drying Times: Touch Dry: 6 hours. Hard Dry: 24 hours. Low temperature/high humidity adversely affects drying time.

Overcoat Time: 12 hours or overnight. Full hardness up to 7 days.

Coverage Guide: 14 square metres per litre

Brush washing/Thinners: White Spirit

HIGH VOC content: 25-50% VOCs (Volatile Organic Compounds) contribute to atmospheric pollution. EU limit value for this product (cat: A/e) : 400g/l (2010). This product contains max 400g/l VOC.

Remove as much of the product as possible from application equipment before washing. Do not empty product into drains or waterways. Some local authorities have special facilities for disposal of waste coatings. To avoid the risk of spillage, always store and transport in secure upright position. During surface preparation, avoid inhalation of dust. Wear a suitable face mask if sanding.

Health, Safety & Environmental Information



WARNING

PAINT UN 1263

Contains: HYDROCARBONS, C9-C11, <2% AROMATICS

Flammable liquid and vapour.

May cause drowsiness or dizziness.

Keep out of reach of children.

If medical advice is needed, have product container or label at hand.

Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Avoid breathing vapours/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Dispose of contents/container in accordance with national regulations.

Repeated exposure may cause skin dryness or cracking.

Contains 2-HYDROXY- 4-N-OCTOXYBENZOPHENONE, and 2-BUTANONE OXIME.

May produce an allergic reaction.



5 015861 004833

Barrettine
TRUSTED BY THE PROFESSIONALS

St. Ivel Way, Warmley, Bristol BS30 8TY.

T +44 (0) 117 960 0060 F +44 (0) 117 935 2437

E sales@barrettine.co.uk www.barrettinePro.co.uk