

Barrettine
TRUSTED BY THE PROFESSIONALS

SPECIALISED
COATINGS & FINISHES

Polyurethane Varnish

A High Durability Varnish

Ideal for internal doors & joinery,
kitchen furniture & worktops.

SATIN

1Le



Polyurethane Varnish

Formulated from a 'single pack' Alkyd Urethane Resin. Once dry, Polyurethane Varnish provides a clear finish for interior wood surfaces where a hard, durable coating is required. It also has exceptional resistance to alcohol, dilute acid, abrasion and heat. The gloss finish gives a superb mirror like effect.

Particularly suitable for use on internal doors and joinery, kitchen furniture and worktops. Additional coats improve the hardness and finish (2-3 coats).

Preparation: Before use, test a small inconspicuous area with all products to be used, to ensure a satisfactory final finish & compatibility. Product has a light amber hue so is not recommended over painted surfaces.

Ensure surfaces are clean, dry and free from wax, oil and dirt. Sand down to remove stains, previous paints or other coatings.

Application: By brush or roller. Stir product thoroughly before use to ensure that any sediment is fully re-dispersed and stir occasionally during use. Un-dispersed sediment can impact the gloss level. Ideal application temperature between 15-25°C. Low temperature/high humidity adversely affects drying time.

Drying Times: Touch Dry: 2 hours. Hard Dry: 12 hours.

Overcoat Time: 12 hours or overnight.

Full Hardness: Up to 7 days.

Coverage Guide: Up to 14 square metres per litre.

Thinners: White Spirit

HIGH VOC content: 25-50% VOCs (Volatile Organic Compounds) contribute to atmospheric pollution. EU limit value for this product (cat: A/e) : 400g/l (2010). This product contains max 400g/l VOC.

Remove as much of the product as possible from application equipment before washing. Do not empty product into drains or waterways. Some local authorities have special facilities for disposal of waste coatings. To avoid the risk of spillage, always store and transport in secure upright position. During surface preparation, avoid inhalation of dust. Wear a suitable face mask if sanding.

Health, Safety & Environmental Information

PAINT UN 1263

WARNING

Contains: HYDROCARBONS, C9-C11,
<2% AROMATICS

Flammable liquid and vapour.

May cause drowsiness or dizziness.

If medical advice is needed, have

product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Avoid breathing vapours, spray. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection, face protection. IF ON SKIN

(or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Dispose of contents and container

to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Repeated exposure may cause skin dryness

or cracking.



CQ90-20NH-700H-58JF



Barrettine Products

St. Ivel Way, Warmley, Bristol. B530 8TY. UK

T: +44 (0) 117 9600060 E: sales@barrettine.co.uk

www.barrettinePro.co.uk

Barrettine (Europe) Ltd

Unit 3D North Point House, North Point Business Park,
New Mallow Road, Cork. T23 AT2P. Ireland

T: +44 (0) 117 9600060