Before use, test a small inconspicuous area to confirm compatibility with the paint system.

Substrates: Designed for wood and masonry. Other substrates may be suitable, subject to the test patch. Not suitable for plastics.

Information

A highly effective paint stripper to remove many types of coatings including most metal/Hammer type paints. Gel consistency ideal for vertical and other less accessible areas to be treated. Read all instructions and safety information before opening this container and use. Coverage: 500ml can remove upto 1.5 square metres of coating depending upon the number of layers / type of paint i.e. one side of a standard door. Non caustic, no neutralising required. Methylene chloride / Dichloromethane free. Use indoors and outdoors. If used indoors make sure there is plenty of ventilation by opening doors and windows. Do not use near naked flames or in conjunction with hot air guns. No Smoking.

Instructions

- Optimum working conditions between 5 and 25° Celsius, avoid direct sunlight.
- Shake container before use.
- Protect all close areas not being stripped with suitable sheeting.
- Light scoring of the coating surface may enhance performance on some coatings, but do not sand if some layers are believed to contain lead (pre 1960 paints).
- Pour a quantity of the product into a suitable container, and replace cap.
- · Apply by brush, add a liberal quantity of product by dabbing onto the coating surface and allow to blister (often occurs within 10-15 minutes), then apply additional product rubbing well into the formed blisters, allow to penetrate for additional 15-30 minutes before trying to remove a small area using a shavehook or stripping knife.

Use a stiff bristled brush for awkward areas. Only apply to an area less than ½ metre square at a time.

- Collect removed waste on e.g. newspaper and allow to dry for a couple of hours before disposing via appropriate waste disposal route. Some local authorities have special facilities for disposing of waste coatings/paints.
- Reapply as necessary to remove all remaining coatings.
- Wipe the surface clean with Barrettine White Spirit or Methylated spirits. Water can be used but it may raise the grain on certain wood substrates. Allow to dry. Finally rub with fine sandpaper or a stainless steel pad before redecorating.
- Remove as much product as possible from equipment before washing them with warm soapy water.
- Do not empty product into drains or watercourses.

Precautions

Caution: Highly Flammable

Ensure working areas are well ventilated at all times. Poor ventilation could allow the build-up of explosive vapours/ mixtures. Wear appropriate personal protective equipment (PPE) such as chemical resistant gloves, overalls and eye/ face protection to protect against splashes. If in doubt speak, to your PPE supplier and show them this label/product, or call us for further advice. Do not use near naked flames or in conjunction with a hot air guns or blow torches. Do not smoke. Ensure the lid is secure and store upright in a cool dry place away from direct sunlight and extremes of temperature.

Very High: VOC content>50%

Health, Safety & Environmental Contains: Hydrocarbons, C9-C11. n-alkanes, isoalkanes, cyclics, < 2% aromatics; 1,3-dioxolane; MEK (METHYL ETHYL KETONE), BUTANONE; Propylene glycol methyl ether; Alcohols, C9-11 ethoxylated, < 2.5 EO. Highly flammable liquid and vapour. Causes serious eye damage. May cause drowsiness or dizziness. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing fume. vapours. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection, face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER, a doctor. Store locked up. Dispose of contents and container to a hazardous or special waste collection point. Do not use in paint spraying equipment.

V.O.C's (Volitile Organic Compounds) Contribute to atmospheric pollution.

Lead Paints: Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

For further advice contact Barrettine Products Ltd: 0117 9600 060



the second of

Barrettine Products: St. Ivel Way, Warmley, Bristol. BS30 8TY. UK T: +44 (0) 117 9600060 E: sales@barrettine.co.uk www.barrettinePro.co.uk

Barrettine (Europe) Ltd

DANGER

Unit 3D North Point House, North Point Business Park, New Mallow Road, Cork.T23 AT2P. Ireland T: +44 (0) 117 9600060



PANTHER

PAINT & VARNISH REMOVER

FAST ACTING. EASY TO APPLY POWERFUL PERFORMANCE METHYLENE CHLORIDE FREE **NON DRIP GEL FORMULA**





Gold winner of the DIY Week Decorating Product of the Year 2011.