RAW LINSEED OIL 2 Litre \oplus

Not Classified according to Regulation (EC) No. 1272/2008 (CLP)

A traditional oil which penetrates and protects unsealed wood by absorbing into the wood leaving a natural finish with a slightly enhanced colour. Suitable for use on oak beams, cricket bats, bean canes and woodcraft applications. Also used for softening putty and as a lubricant for French Polishing.

Food/Toy safe when dry, certified by EN 1186:2002 & EN71:3.

PREPARATION AND APPLICATION:

Test in an inconspicuous area before use.

Raw Linseed Oil must be thoroughly shaken before use.

Ensure surfaces to be treated are uncoated, dry and clean - free from wax / dirl. Oily woods require wiping with white spirit before application. For new wood it is recommended to dilute the first 2 coats with 10 - 30% Turpentine / White Spirit. Rub into the wood using a lint-free cloth or brush onto the surface. Leave for 10-15 minutes then remove excess with a clean lint-free cloth. Apply a minimum of 3 coats allowing 12-24 hours between coats. Leave the final coat to absorb / dry for a few days before use. Exterior wood will require regular re-oiling. Clean any equipment with Barrettine White Spirit. Coverage 8-10 square metres per litre depending upon wood porosity.

PRECAUTIONS:

Cloths used for oiling may spontaneously combust, immediately after use soak them in soapy water and then lay them flat outside on a non-combustible surface to dry. Keep container upright and secure at all times.

Safety data sheet available on request.

Dispose of contents/container in accordance with local/national regulations. Keep out the reach of children.

<u>Barrettine</u>

Barrettine Products
St. Ivel Way, Warmley,
Bristol BS30 8TY. UK
T: +44 (0) 117 960 0060
E: sales@barrettine.co.uk



Barrettine (Europe) Ltd Unit 3D North Point House, North Point Business Park, New Mallow Road, Cork. 123 AT2P. Ireland T: +353 21 206 6530