

DECORATE

TEREBINE DRIERS

A specially blended solution of liquid metallic driers to speed up the drying time of most solvent / oil based conventional air-drying paints during cold weather or adverse conditions.



250ml e

Barrettine

Instructions for use: Add a maximum of 10 ml per 1 litre of paint and mix thoroughly (cap holds 10-11mls).

Suitable for use with Gloss Oil Paints, Polyurethanes, Varnishes and most conventional air-drying paints.

Caution: Not suitable for water based or cellulose paints. It is recommended to conduct a test to ensure compatibility with other paint resin systems and that the dry paint film finish is acceptable.

Recommended for use only when the ambient temperature is between 2 - 10 Celsius.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; Naphtha (petroleum), hydrotreated heavy < 0.1% Benzene; Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics. Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing fume, mist, spray, vapours. Use only outdoors or in a well-ventilated area. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Repeated exposure may cause skin dryness or cracking.

UFI: 9HCO-Q04U-N00W-1EST

UN No. 1263



DANGER

Barrettine Products: St. Ivel Way, Warmley, Bristol. BS30 8TY. UK

T +44 (0) 117 9600060 E sales@barrettine.co.uk www.barrettinePro.co.uk

Barrettine (Europe) Ltd: Unit 3D North Point House, North Point Business Park, New Mallow Road, Cork. T23 AT2P. Ireland T +353 21 206 6530

R2