

WHITE KNOTTING

A quality 'clear' knotting made from White Shellac. For use on knots and resinous areas prior to painting/varnishing.

Reduces discolouration of topcoats when sealing knots under woodstains, varnishes and lighter coloured paints.

Suitable for use under solvent and waterbased paints.*

UFI: WX00-F081-0001-PF3V



250mle

Barrettine

SHAKE WELL For interior and exterior use

Instructions for use: Ensure all surfaces are sound, clean dry and free from any contaminants. Sand down thoroughly ready for priming and ensure all dust is removed. Wipe knots with Methylated Spirit prior to applying knotting. Apply one coat of knotting over and around all knots and resinous areas working well in, ensuring all knots are properly sealed. After a minimum of 30 minutes a second coat must be applied if subsequently finishing with a water based coating and recommended for solvent based coatings. Over coating possible after 1-2 hours. If knots are exuding excessive resin it is recommended to remove them and make good with wood filler. Clean brushes with Barrettine Methylated Spirits or Cellulose Thinners. *Caution: We recommend doing a test area first to ensure compatibility with too coats/oaint systems to be used.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Highly flammable liquid and vapour. Causes serious eye irritation. May cause damage to organs. If medical advice is needed, have product container or label at hand. Keep out of reach of thildren. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking, Wash hands thoroughly after handling. Wear protective gloves, eye protection. IF ON SKIN (or hair.' Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Dispose of contents, container to a hazardous or special waste collection point.

Contains: Whethanol.

Very high: VOC content >50%

VOCs (Volatile Organic Compounds) Contribute to atmospheric pollution.
EU limit value for this product (A/h 750 g/l (2007) 750 g/l (2010)
This product contains max 614 g/l VOC



Danaer

Barrettine Products - St. Ivel Way, Warmley, Bristol. BS30 8TY. UK
T: +44 (0) 117 9600060 E: sales@barrettine.co.uk www.barrettinePro.co.uk

Barrettine (Europe) Ltd - Unit 3D North Point House, North Point Business Park, New Mallow Road, Cork. T23 AT2P. Ireland T: 435-21 206 653-21