

BARRETTINE NOURISH AND PROTECT COLOURS+

WOOD PRESERVATIVE FOR AMATEUR/PROFESSIONAL USE AGAINST WOOD ROTTING FUNGI, WOOD STAINING FUNGI AND WOOD DESTROYING INSECTS.

PRODUCT DESCRIPTION: This is a low odour, solvent-borne, ready to use wood preservative which is odourless once dry. It actively protects against wood destroying & discolouring fungi and wood boring insects. The high penetrating ability of the product transports the actives into the wood and provides some vapour permeability, whilst coloured versions also contain UV fade resistant pigments, providing some protection from damaging sunlight. As the finish is semi-transparent, the natural texture of the grain is visible and the sheen is matt to satin, depending on wood smoothness and number of coats.

READ ALL PRECAUTIONS & THE FULL LABEL BEFORE USE.

RANGE OF USE: Outside applications including inner and outer frames of external joinery, doors, windows, facades, carports, shutters, summer houses, gates and balcony railings. Also suitable for wood resting on the ground / hardstanding and not in constant contact with water, such as garden furniture. Not suitable for any in-ground use or where the wood is subjected to continual wetting, e.g. streams or ponds. If used on Wooden Garden furniture, make sure the coating has fully dried/cured and is colour fast before use. The results and timing can vary due to atmospheric weather conditions and wood type. Natural oily/resinous woods and tight grain hardwoods can take longer to dry and completely cure. To be sure there is no risk of colour transfer from the treated wood/furniture onto clothing, we recommend running a white lint-free cloth over the surface and inspect for any colour rub off. If colour transfer occurs, the treated article may need a longer drying time. Due to the nature of certain resinous woods, a sealer/topcoat may be required. We recommend carrying out a test area first. Further information at: www.barrettinePro.co.uk

INSTRUCTIONS FOR USE: Colour swatches are an indication only of the product applied to clean, pale timber. The final colour and finish can vary considerably due to the age, type & condition of the area being treated. Wood surfaces must be clean and dry before treating. Always test an inconspicuous area before starting any project to check product suitability, compatibility and final dry colour. If using a stain / wood dye, apply the colourant before the Preserver and test the effect on an off-cut.

New wood: If fungal contamination suspected, clean with Knockout Mould & Mildew Cleaner. Tannin-rich woods should be weathered before use.

Renovation: All coatings should be completely removed. Pre 1960's paint may contain lead, take special precautions. If necessary, grey or deteriorated wood should be sanded down to a clean, sound surface or treated with Barrettine Wood Reviver. Remove dust by wiping with Barrettine White Spirit or Methylated Spirits.

Application method/coverage:

STATUTORY CONDITIONS OF APPROVAL RELATING TO USE FOR USE ONLY AS A WOOD PRESERVATIVE

READ ALL PRECAUTIONS BEFORE USE. HSE No. 10944 PCS No. 98437 Users must comply in full with all their legal responsibilities under the control of Pesticides Regulations 1986 (as amended), including complying with all Conditions of Approval. **APPLICATION METHOD/COVERAGE: Amateur:** BRUSH AND ROLLER. **Professional:** BRUSH, DIP AND ROLLER. APPLY 180 ml OF PRODUCT PER M² OF TIMBER SURFACE. **DIPPING:** DIP TIMBER IN PRODUCT FOR AT LEAST 3 MINS. Effective Against Wood Destroying Fungi, Blue Stain and Wood Boring Insects at 180 ml/m².

Application temperature: Ideally between 10 – 30°C. Wood should be frost-free when treated.

Amateur / Professional uses: Protect environment (e.g. Soil, plants, aquatic environment) from splashes. Do not apply in damp conditions or if rain is imminent. Apply thinly and evenly using a synthetic brush designed for solvent-borne products, in the direction of the wood grain. Ensure end grain is thoroughly treated along with cut and drilled areas and reseal container after use. 2 coats minimum are recommended, depending on wood species and surface characteristics.

Drying time: 12 h under normal conditions (20°C/65% rel. humidity). Allow 6–12 hours drying time (touch dry) between coats. Low temperatures, increased humidity and composition of some wood types may increase drying time. Multiple applications will provide a darker finish and smoother wood will increase the sheen.

Cleaning of tools: Barrettine White Spirit or Brush Cleaner, immediately after use.

Maintenance/Compatibility: Maintenance requirements will depend on exposure and weathering. A top coat is not necessary over this product but can be applied after 24 h drying time (normal conditions). Barrettine Decking Oil, Log Cabin Treatment or a varnish/ sealer (solvent or water based) will extend protection. Compatibility and adhesion should be tested in a sample area first.

FIRST AID MEASURES: SKIN CONTACT: Immediately remove all contaminated clothing, and wash skin with plenty of water and soap. Seek medical advice if symptoms occur.

EYE CONTACT: Rinse immediately with plenty of water and seek medical attention if symptoms occur.

IF SWALLOWED: Rinse mouth with water and give small amounts of water to drink (not in the case of loss of consciousness). Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Seek medical attention if symptoms occur.

AFTER INHALATION: Move exposed person into fresh air and keep warm and at rest. Provide artificial respiration by a trained person if breathing is irregular or arrested. It may be dangerous to the person providing aid by mouth-to-mouth resuscitation. Seek medical advice if symptoms are severe or long lasting. If unconscious, place in recovery position and get medical attention immediately.

Barrettine Products

St. Ivel Way, Warmley, Bristol. BS30 8TY. UK
T: +44 (0) 117 9600060 E: sales@barrettine.co.uk
www.barrettinePro.co.uk

SHAKE WELL

BEFORE & DURING USE FOR AT LEAST 1 MINUTE

IN GENERAL: Show this label if medical advice is needed.

PRECAUTIONARY INFORMATION: USE ONLY AS DESCRIBED ON THE LABEL.

General precautions recommended for handling wood preservative should be observed, e.g. Wear appropriate personal protective equipment (PPE) such as chemical resistant gloves, overalls and eye/face protection to protect against splashes. If in doubt, speak to your PPE supplier and show them this label/product, or call us for further advice. Do not eat, drink or smoke whilst using. Handle product and dry freshly treated wood in areas with good ventilation and protect from rain until completely dry. Do not breathe sanding dust. During application to in situ timbers and during drying, do not contaminate soil and surface waters with product. Do not empty into drains or allow this product to reach aquatic environments, the ground or the sewer system. For Professional use, freshly treated timber must be stored after treatment under shelter or on impermeable hardstanding to prevent direct losses to soil or water. Any losses must be collected for reuse or disposal.

STORAGE: Store in original containers, tightly closed, between 0°C and 30°C.

DISPOSAL INFORMATION: Completely empty cans can be recycled as normal. Dispose of left-over product in the original container, in compliance with local regulations. Do not discharge product residues or cleaning wastes into the sewer system, drains, waterways or soil. Do not reuse empty containers.

European Waste Code (EWC)-Code

03 02 02: Organochlorinated wood preservative.

20 01 27: Municipal wastes (household waste and similar commercial, industrial and institutional wastes) including separately collected fractions : paint, inks, adhesives and resins containing dangerous substances.

RISK MITIGATION MEASURES

This material and its container must be disposed of in a safe way. DO NOT CONTAMINATE FOOD STUFFS, EATING UTENSIL OR FOOD CONTACT SURFACES. WASH HANDS AND EXPOSED SKIN before meals and after use. KEEP IN A SAFE PLACE. UNPROTECTED PERSONS AND ANIMALS SHOULD BE KEPT AWAY FROM TREATED AREAS FOR 48 HOURS OR UNTIL SURFACES ARE DRY. AVOID ALL CONTACT WITH PLANT LIFE. COVER ALL STORAGE WATER TANKS before application. ALL BATS ARE PROTECTED UNDER THE WILDLIFE & COUNTRYSIDE ACT 1981. BEFORE TREATING ANY STRUCTURE USED BY BATS, CONSULT NATURAL ENGLAND, SCOTTISH NATURAL HERITAGE OR THE COUNTRYSIDE COUNCIL FOR WALES. HAZARDOUS TO BEES. DO NOT USE ON BEEHIVES OR BEE KEEPING EQUIPMENT. 3-iodo-2-propynyl-N-BUTYL CARBAMATE is carbamate compound which has weak anticholinesterase activity. DO NOT USE if under medical advise not to work with anticholinesterase compounds. FOR OUTDOOR USE. Also for use on windows/frames, external doors/frames (internal & external sections).

ADDITIONAL RISK MITIGATION MEASURES FOR USE BY PROFESSIONAL OPERATORS

Avoid excessive contamination of coveralls. The COSHH (Control of Substances Hazardous to Health) Regulations 2002 (as amended) apply to the use of this product at work. Refer to www.hse.gov.uk/pubns/guidance/sseries.htm

To avoid risk to man and the environment, comply with instructions for use. **ACTIVE INGREDIENT:** 3-iodo-2-propynyl butylcarbamate (IPBC) 0.624% w/w, Tebuconazole 0.284% w/w and Permethrin 0.06% w/w.

EXPIRY DATE: 2 years from production date.

OUT OF HOURS EMERGENCY TELEPHONE NO. +44 (0) 1270 502891

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Contains: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics.



May be fatal if swallowed and enters airways. Very toxic to aquatic life with long lasting effects. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Avoid breathing fume, mist, spray, vapours. Wear protective gloves, protective clothing, eye protection. If SWALLOWED: Immediately call a POISON CENTER, a doctor. Do NOT induce vomiting. Collect spillage. Store locked up. Dispose of contents, container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Repeated exposure may cause skin dryness or cracking. Contains 3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate(55406-53-6). May produce an allergic reaction.

Use biocides safely.

Always read the label and product information before use.

VERY HIGH VOC CONTENT >50%

VOCs (Volatile Organic Compounds) Contribute to atmospheric pollution.

Barrettine (Europe) Ltd

Unit 3D North Point House, North Point Business Park,
New Mallow Road, Cork. T23 AT2P. Ireland
T: +353 21 206 6530


Barrettine
TRUSTED BY THE PROFESSIONALS

PREMIER COLOURS

WOOD PRESERVER

NOURISH AND PROTECT

OIL BASED* WATER BASED



✓ OIL/SPIRIT BASED
✓ DEEPER PENETRATION
✓ GREATER PROTECTION

* Based on internal testing

*Regular treatment gives
Superb water repellency*



UFI: 1Q10-00FK-R00G-NHCF

**SHAKE WELL
BEFORE & DURING USE**
(FOR AT LEAST ONE MINUTE)

Barrettine
TRUSTED BY THE PROFESSIONALS



PREMIER COLOURS

BARRETTINE NOURISH AND PROTECT COLOURS+

WOOD PRESERVER

**PROTECTS AGAINST
WOOD BORING INSECTS, WOOD ROTTING FUNGI & BLUE STAIN**

✓ **HIGH LEVEL, LONG LASTING PROTECTION & PRESERVATION**

✓ **SUPERB QUALITY WATER REPELLENT RESINS**


✓ **UV FADE RESISTANT COLOUR PIGMENTS***

* UV resistance does not apply to the 'Clear' option


**RELEASE
POURING SPOUT
TO POUR PRODUCT.**

For full instructions,


SCAN ME



The following colours are also available
in our Wood Preserver Range.




RED CEDAR



DARK BROWN




CLEAR



LIGHT BROWN




BLACK



GOLDEN BROWN



SUMMER TAN



HOLLY GREEN

The colour swatches are an indication only and representative of the product applied to clean new/pale timber. The final colour finish can vary considerably due to the age, type & condition of the timber being treated. We always recommend carrying out a test area first in an inconspicuous area to make sure you are happy with the final dried colour.

**SHAKE WELL
BEFORE & DURING USE**
(FOR AT LEAST ONE MINUTE)

NOURISH AND PROTECT

**DEEP PENETRATING
OIL/SPIRIT LOW ODOUR
BASED FORMULA**

5L e

5 Litre e