

# DANISH OIL

A blend of rich oils, including Tung Oil, providing an attractive water repellent low lustre natural finish to woods. Suitable for interior and exterior use including doors, panelling, furniture, wood decorations and wood turning.

Food/Toy safe when dry, certified by EN 1186:2002 & EN71:3.

## INSTRUCTIONS

Wear appropriate personal protective equipment (PPE) such as chemical resistant gloves, overalls and eye/face protection to protect against splashes. If in doubt speak, to your PPE supplier and show them this label/product, or call us for further advice. Shake well before use. Carry out a small test patch first to determine an acceptable finish on an off-cut or unseen area. Ensure surfaces to be treated are uncoated, dry and clean - free from wax / dirt. Oily woods require wiping with white spirit before application. Shake well and decant product into a paint scuttle/kettle. Apply carefully with a lint-free cloth or brush and avoid excess material laying on the top. **Leave for 10-15 minutes then remove any remaining excess with a clean lint-free cloth.** Apply a minimum of 2 coats internally on new wood allowing 6-10 hours between coats. Previously oiled wood can be partially sealed, especially if a slight gloss is evident, that prevents any fresh application of oil to penetrate. To prepare the wood surface use a very fine stainless steel wool lightly rubbing in the direction of the grain and wipe with white spirit to remove residues prior to reapplication of oil. For exterior use apply a minimum of 3 coats ensuring any end grain wood is very thoroughly treated. Exterior wood will require regular re-oiling. Allow minimum 24 hours to fully dry during which time protect from water. Ideally apply between 10-25 Celsius, do not apply when ambient or surface temperature below 5 Celsius. Coverage 6-10 square metres per litre depending upon wood porosity. Clean brushes whilst wet with Barretline white spirit.

## PRECAUTIONS

Cloths used for oiling may spontaneously combust, immediately after use soak them in soapy water and then lay them flat outside on a non-combustible surface to dry.

## HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics, Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics. Flammable liquid and vapour. May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing fume, mist, spray, vapours. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection.

IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Repeated exposure may cause skin dryness or cracking.



**VOC Statement:** EU Limit value for this product (Cat A/h) 750g/L (2010)  
This product contains max 536g/L VOC

**Barretline Products**  
St. Ivel Way, Warmley, Bristol. BS30 8TY. UK  
T: +44 (0) 117 9600060  
E: sales@barretline.co.uk  
www.barretlinePro.co.uk

**Barretline (Europe) Ltd**  
Unit 3D North Point House,  
North Point Business Park,  
New Mallow Road, Cork. T23 AT2P. Ireland  
T: +353 21 206 6530

▲  
**RELEASE  
POURING SPOUT  
TO POUR PRODUCT.**

For full instructions,

📱 **SCAN ME**



**Barretline**  
TRUSTED BY THE **PROFESSIONALS**

PREMIER

# DANISH OIL

A blend of rich oils, including Tung Oil, providing an attractive water repellent low lustre natural finish to woods.  
**For interior and exterior wooden surfaces.**

**NOURISH**  
AND  
**PROTECT**



EN1186:2002 & EN71:3

**5 Litre e**

UFI: 1220-1075-Y00F-9VPQ



5 015861 510501