



SAFETY DATA SHEET

LOG CABIN & COMPLETE DECKING TREATMENT - CLEAR

Page: 1

Compilation date: 11/05/2015

Revision date: 18/04/2019

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: LOG CABIN & COMPLETE DECKING TREATMENT - CLEAR

Product code: LCDTGEN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Consumer Use. Professional Use. Wood treatment.

1.3. Details of the supplier of the safety data sheet

Company name: J.V. Barrett & Co Ltd

St Ivel Way

Warmley

Bristol

BS30 8TY

United Kingdom

Tel: 01179600060

Fax: 01179352437

Email: sales@barrettine.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 1179 600060 (Office hours only 8am - 5pm Mon- Thurs. 8 am - 4.30 pm
Fri.) +44 (0) 1270 502891 (Out of hours emergency number)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226; STOT SE 3: H336; Asp. Tox. 1: H304; -: EUH066; -: EUH208

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. Contains 3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate. May produce an allergic reaction. Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.

2.2. Label elements

Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

[cont...]

SAFETY DATA SHEET

LOG CABIN & COMPLETE DECKING TREATMENT - CLEAR

Page: 2

EUH208: Contains 3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H336: May cause drowsiness or dizziness.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

GHS08: Health hazard



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233: Keep container tightly closed.

P261: Avoid breathing fume, vapours, mist, spray.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P362+P364: Take off contaminated clothing and wash it before reuse.

P501: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS - REACH registered number(s): 01-2119463258-33-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
919-857-5	-	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	50-70%

[cont...]

SAFETY DATA SHEET

LOG CABIN & COMPLETE DECKING TREATMENT - CLEAR

Page: 3

PARAFFIN WAX - REACH registered number(s): 01-2119488075-30-XXXX

232-315-6	8002-74-2	Substance with a Community workplace exposure limit.	-	1-10%
-----------	-----------	--	---	-------

3-IODO-2-PROPYNYL BUTYLCARBAMATE - REACH registered number(s): 01-2120762115-60-XXXX

259-627-5	55406-53-6	-	Acute Tox. 3: H331; Acute Tox. 4: H302; STOT RE 1: H372; Eye Dam. 1: H318; Skin Sens. 1: H317; Aquatic Acute 1: H400; Aquatic Chronic 1: H410	0.3-1%
-----------	------------	---	---	--------

COBALT BIS(2-ETHYLHEXANOATE) - REACH registered number(s): 01-2119524678-29-XXXX

205-250-6	136-52-7	-	Aquatic Acute 1: H400; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Repr. 2: H361f; Skin Sens. 1A: H317	<0.3%
-----------	----------	---	---	-------

2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT - REACH registered number(s): 01-2119979088-21-XXXX

245-018-1	22464-99-9	-	Repr. 2: H361	<0.3%
-----------	------------	---	---------------	-------

1-ACETYL-4-(3-DODECYL-2,5-DIOXO-1-PYRROLIDINYL)-2,2,6,6-TETRAMETHYLPYPERIDINE - REACH registered number(s): 01-0000015927-59-XXXX

411-930-5	106917-31-1	-	Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	<0.3%
-----------	-------------	---	---	-------

Section 4: First aid measures

4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.
- Eye contact:** Bathe the eye with running water for 15 minutes. Obtain medical attention if pain, blinking or redness persist.
- Ingestion:** Wash out mouth with water. Do not induce vomiting. Transfer to hospital as soon as possible.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** There may be mild irritation at the site of contact.
- Eye contact:** There may be irritation and redness.
- Ingestion:** There may be irritation of the throat. May be fatal if swallowed and enters airways.
- Inhalation:** Drowsiness or mental confusion may occur.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Treat Symptomatically.

[cont...]

SAFETY DATA SHEET

LOG CABIN & COMPLETE DECKING TREATMENT - CLEAR

Page: 4

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Sand.
Do not use water jet

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes. Contain the spread of the firefighting media. Do not allow run-off from firefighting to enter drains or water courses.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

[cont...]

SAFETY DATA SHEET

LOG CABIN & COMPLETE DECKING TREATMENT - CLEAR

Page: 5

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

COBALT BIS(2-ETHYLHEXANOATE)

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.1 mg/m ³	-	-	-

DNEL/PNEC Values

Hazardous ingredients:

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

Type	Exposure	Value	Population	Effect
DNEL	Dermal (repeated dose)	208 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation (repeated dose)	871 mg/m ³ /8H	Workers	Systemic
DNEL	Dermal (effects on fertility)	125 mg/kg bw/day	Consumers	Systemic
DNEL	Inhalation (repeated dose)	185 mg/m ³ /24H	Consumers	Systemic
DNEL	Oral	125 mg/kg bw/day	Consumers	Systemic

3-IODO-2-PROPYNYL BUTYLCARBAMATE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	70 µg/m ³	Workers	Systemic
DNEL	Inhalation (repeated dose)	23 µg/m ³	Workers	Systemic
DNEL	Inhalation	1.16 mg/m ³	Workers	Local
DNEL	Inhalation (repeated dose)	1.16 mg/m ³	Workers	Local
DNEL	Dermal (repeated dose)	2 mg/kg bw/day	Workers	Systemic
PNEC	Fresh water	500 ng/l	-	-
PNEC	Fresh water sediments	17 µg/kg	-	-
PNEC	Marine water	46 ng/l	-	-
PNEC	Marine sediments	1.6 µg/kg	-	-
PNEC	Microorganisms in sewage treatment	440 µg/l	-	-
PNEC	Soil (agricultural)	5 µg/kg	-	-

COBALT BIS(2-ETHYLHEXANOATE)

Type	Exposure	Value	Population	Effect
DNEL	Inhalation (repeated dose)	235 µg/m ³	Workers	Systemic
DNEL	Inhalation (repeated dose)	37 µg/m ³	General Population	Systemic
DNEL	Oral (repeated dose)	27.6 µg/kg bw/day	General Population	Systemic

[cont...]

SAFETY DATA SHEET

LOG CABIN & COMPLETE DECKING TREATMENT - CLEAR

Page: 6

PNEC	Fresh water	600 ng/l	-	-
PNEC	Fresh water sediments	9.5 mg/kg	-	-
PNEC	Marine water	2.36 µg/l	-	-
PNEC	Marine sediments	9.5 mg/kg	-	-
PNEC	Microorganisms in sewage treatment	370 µg/l	-	-
PNEC	Soil (agricultural)	10.9 mg/kg	-	-

2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT

Type	Exposure	Value	Population	Effect
DNEL	Inhalation (repeated dose)	32 mg/m ³	Workers	Systemic
DNEL	Inhalation (repeated dose)	8 mg/m ³	General Population	Systemic
DNEL	Dermal (repeated dose)	6.49 mg/kg bw/day	Workers	Systemic
DNEL	Dermal (repeated dose)	3.25 mg/kg bw/day	General Population	Systemic
DNEL	Oral (repeated dose)	2.5 mg/kg bw/day	General Population	Systemic
PNEC	Fresh water	360 µg/l	-	-
PNEC	Fresh water sediments	6.37 mg/kg	-	-
PNEC	Marine water	36 µg/l	-	-
PNEC	Marine sediments	637 µg/kg	-	-
PNEC	Microorganisms in sewage treatment	71.7 mg/l	-	-
PNEC	Soil (agricultural)	1.06 mg/kg	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Avoid release to the environment

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Light Brown

Odour: Hydrocarbons

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Insoluble

Viscosity: No data available.

[cont...]

SAFETY DATA SHEET

LOG CABIN & COMPLETE DECKING TREATMENT - CLEAR

Page: 7

Boiling point/range°C: 150-200
Flammability limits %: lower: No data available.
Flash point°C: 38
Autoflammability°C: No data available.
Relative density: 0.78-0.81
VOC g/l: No data available.

Melting point/range°C: No data available.
upper: No data available.
Part.coeff. n-octanol/water: No data available.
Vapour pressure: No data available.
pH: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Extremely high or low temperatures. Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

GASES	RBT	24H LD50	> 5000	mg/kg
ORAL	RAT	LD50	> 5000	mg/kg
VAPOURS	RAT	8H LC50	> 5000	mg/m3

[cont...]

SAFETY DATA SHEET

LOG CABIN & COMPLETE DECKING TREATMENT - CLEAR

Page: 8

PARAFFIN WAX

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

3-iodo-2-propynyl butylcarbamate

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	300 to 500	mg/kg
VAPOURS	RAT	4H LC50	0.67	mg/l

2-ethylhexanoic acid, zirconium salt

DERMAL	RAT	LD50	2000	mg/kg
ORAL	RAT	LD50	2043-5000	mg/kg
VAPOURS	RAT	8H LC50	110	mg/m3

1-acetyl-4-(3-dodecyl-2,5-dioxo-1-pyrrolidinyl)-2,2,6,6-tetramethylpiperidine

ORAL	RAT	LD50	>3000	mg/kg
VAPOURS	RAT	4H LC50	2.61	mg/l

Relevant hazards for product:

Hazard	Route	Basis
STOT-single exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat. May be fatal if swallowed and enters airways.

Inhalation: Drowsiness or mental confusion may occur.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

ALGAE	72H EbL50	>1000	mg/l
ALGAE	72H ErL50	>1000	mg/l
Daphnia magna	48H EL50	>1000	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LL50	>1000	mg/l

[cont...]

SAFETY DATA SHEET

LOG CABIN & COMPLETE DECKING TREATMENT - CLEAR

Page: 9

PARAFFIN WAX

ALGAE	NOEL	>100	mg/l
Daphnia magna	EL50	>10000	mg/l
Daphnia magna	NOEL	10	mg/l
FISH	LL50	>100	mg/l

3-IODO-2-PROPYNYL BUTYLCARBAMATE

Daphnia magna	48H EC50	0.16	mg/l
RAINBOW TROUT (<i>Oncorhynchus mykiss</i>)	96H LC50	0.67	mg/l
Scenedesmus Subspicatus	72H ErC50	0.053	mg/l

2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT

ALGAE	96H EC10	32	mg/l
DAPHNIA	48H EC50	62.5	mg/l
FISH	96H LC50	100	mg/l

1-ACETYL-4-(3-DODECYL-2,5-DIOXO-1-PYRROLIDINYL)-2,2,6,6-TETRAMETHYLPIPERIDINE

Daphnia magna	48H EC50	0.27	mg/l
FISH	96H LC50	>0.5	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Avoid release to the environment.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 03 02 05

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]

SAFETY DATA SHEET

LOG CABIN & COMPLETE DECKING TREATMENT - CLEAR

Page: 10

Section 14: Transport information

14.1. UN number

UN number: UN1268

14.2. UN proper shipping name

Shipping name: PETROLEUM PRODUCTS, N.O.S.
(HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2%
AROMATICS; 3-iodo-2-propynyl butylcarbamate)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment
Regulation (EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.
EUH208: Contains 3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl
butylcarbamate. May produce an allergic reaction.
H226: Flammable liquid and vapour.
H302: Harmful if swallowed.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.

[cont...]

SAFETY DATA SHEET

LOG CABIN & COMPLETE DECKING TREATMENT - CLEAR

Page: 11

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H336: May cause drowsiness or dizziness.

H361: Suspected of damaging fertility or the unborn child.

H361f: Suspected of damaging fertility.

H372: Causes damage to organs through prolonged or repeated exposure.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.