

Attention! Read all instructions & Test Patch information before use.

Peelaway® Marine is specially formulated to effectively remove multiple layers of anti-foul coatings with one application saving time by reducing the need for repeated scraping. Its patented water based poultice system means the product remains active and works without rapidly drying out. The special poultice blanket supplied enables stripped anti-foul paint to be collected easily and so reduces boatyard/dockside contamination risk.

Peelaway® Marine is a light paste consistency and is easy to apply to vertical surfaces and difficult shapes. It can be applied with a brush or trowel and for larger areas an airless sprayer can be used. **Always carry out a test patch before general application.** Suitable for most hull types including GRP, wood, steel and concrete.

LIMITATIONS: **Peelaway® Marine** will work slower under 5 degrees and will stop working below freezing. It will not remove certain two pack epoxy coatings, enamels or cement based paints.

PREPARATION: Please read all the instructions and safety information before starting work.

Clean and prepare the work area removing any built up accumulations of fouling or blistered old anti foul coating. Cover any surfaces not intended to be stripped with polythene sheet and tape.

TEST PATCH AREAS: It is often impossible to know the type and build depth of anti-fouling before coatings are removed. It is essential to apply a test patch to an area typical of the surface to be stripped to ensure the results will be satisfactory. This will also indicate the dwell time required and thickness of paste to be applied. It is the responsibility of the user to ensure the suitability of the product for each individual application. Once a small test patch has been successful we recommend wider tests across the surface to more accurately determine the application thickness and time required for the stripping process. **Note:** The film thickness of anti-fouling can vary across the length of the hull. **Peelaway® Marine** is safe to use on GRP/gel coat finishes based on our internal tests where product was not left on for more than 48 hours. Some discolouration of treated area may occur. Remove **Peelaway Marine** as soon as the coatings have been removed. Barrettine accepts no responsibility for damage or unsatisfactory results caused by the use of **Peelaway® Marine**.

SAFETY: Wear coveralls, chemical resistant gloves, face mask and eye protection. If in doubt, show this label/product to your PPE supplier or call us for further advice. Ensure adequate cross ventilation if indoors. Keep product away from children and animals. Store product in a cool dry area and always replace the lid after use. In case of spillage, wash the affected area with plenty of water. See Health safety and Environmental information box below for full regulatory warnings.

COVERAGE: Coverage will vary from project to project. Determining factors will include; the number of layers to be stripped and the type and age of anti-foul to be stripped. The **test patch** referred to above is vital to determine coverage for each particular application but as a rough guide 1kg will cover 2-4m².

APPLICATION: Stir well before use. Depending on test results apply up to 3mm thick.

Brush or trowel – Apply evenly with brush or trowel working into crevices, including on wooden hulls where planks overlap. Ensure raised edges and corners are covered well. Then apply a second coat to the final tested thickness. Finally, lay on the poultice with printing facing outwards, gently rubbing to exclude trapped air bubbles. Work in manageable areas which can be removed within the time scale indicated by the **test patch**.

Airless Spray – When using an airless spray applicator add water to dilute up to a maximum of 20%. Spray evenly up to a maximum of 3mm. Finally, lay on the poultice with printing facing outwards, gently rubbing to exclude trapped air bubbles. Work in manageable areas which can be removed within the time scale indicated by the **test patch**. Dwell time can be between 30 minutes and 24-48 hours as indicated by the results of the **test patch**. When using on GRP/Gel coat do not leave on longer than 48 hours.

External use may be affected by extremes of weather and treated areas should be monitored and further protected if required.

REMOVAL: Slide scraper into paste and paint, keeping the paint, paste and cover together as much as possible. Take care not to gouge/scratch the gel coat. Certain paints can be softened but not easily removed with the scraper, in which case try rubbing with a scouring pad with water or mineral spirits until the original surface is revealed and wash down with water. Steam cleaning or pressure washing may also aid removal of residues. Alternatively any remaining residue pre-softened can be removed in a few hours with a further application of **Peelaway® Marine**. Once all the old anti-fouling paint has been removed, any remaining residues of **Peelaway® Marine** must be cleaned/washed away. Allow the cleaned surface to dry thoroughly before re-coating

DISPOSAL: Collect all residues and dispose according to local regulations for this type of waste.

IMPORTANT INFORMATION TO PURCHASER:

Information is given on the basis of our research and the research of others. However, no guarantee can be made, as we cannot anticipate every variation in site conditions, surface coating and the methods of application. Purchasers shall be responsible for making their own tests to determine the suitability of this product for a particular purpose. The sellers and manufacturers only obligation is to replace any product proven to be defective and shall not be liable for any loss, damage or injury direct or consequential, arising out of the use or inability to use this product.

For more information visit: www.peelawaymarine.co.uk

Barrettine Products Ltd

St. Ivel Way, Warmley, Bristol BS30 8TY.
T: 0117 960 0060 E: sales@barrettine.co.uk
www.barrettinePro.co.uk

Barrettine (Europe) Ltd

Unit 3D North Point House, North Point Business Park,
New Mallow Road, Cork. T23 AT2P. Ireland
T: +44 (0) 117 9600060

HEALTH & SAFETY

CONTAINS: BENZYL ALCOHOL

WARNING

Harmful if swallowed or if inhaled.

Keep out of reach of children. Do

not breathe fume, vapours. Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product. Use only

outdoors or in a well-ventilated

area. IF SWALLOWED: Immediately

call a POISON CENTER, a doctor.

Dispose of contents, container to a

hazardous or special waste collection point.

PEELAWAY formulation, cover and trade name is sole property of Peelaway Ltd.

