

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Product name : Bio Ethanol Liquid  
UFI : SA80-Y0M5-A00K-JT7E  
Product code : BIETGEN

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Intended for general public  
Main use category : Professional use, Consumer use  
Use of the substance/mixture : Fuels

**1.2.2. Uses advised against**

Restrictions on use : Not Otherwise Specified

**1.3. Details of the supplier of the safety data sheet****Supplier**

J.V. Barrett & Co. Ltd Ltd  
St Ivel Way  
Warmley  
United Kingdom BS30 8TY Bristol  
United Kingdom  
T +44 (0)1179 60 00 60  
[sales@barrettine.co.uk](mailto:sales@barrettine.co.uk), [www.barrettine.co.uk](http://www.barrettine.co.uk)

**EU**

Barrettine (Europe) Ltd Ltd  
Unit 3D North Point House, North Point Business Park,  
New Mallow Road  
Ireland T23 AT2P Cork  
Ireland  
T +353 21 206 6530  
[sales@barrettine.co.uk](mailto:sales@barrettine.co.uk), [www.barrettine.co.uk](http://www.barrettine.co.uk)

**1.4. Emergency telephone number**

Emergency number : +44 (0) 1179 600060 (Office hours only 8am - 5pm Mon- Thurs. 8 am - 4.30 pm Fri.)  
+44 (0) 1865 407333 (Out of hours emergency number)

Country/Area	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 2 H225  
Serious eye damage/eye irritation, Category 2 H319  
Full text of H- and EUH-statements: see section 16

**Adverse physicochemical, human health and environmental effects**

Highly flammable liquid and vapour. Causes serious eye irritation.

# Bio Ethanol Liquid


## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.  
H319 - Causes serious eye irritation.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 - Wear protective gloves, eye protection.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P501 - Dispose of contents to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Child-resistant fastening

: Not applicable

Tactile warning

: Applicable

### 2.3. Other hazards

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethanol; ethyl alcohol	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-43	$\geq 90 - < 95$	Flam. Liq. 2, H225 Eye Irrit. 2, H319
isopropanol	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558-25	$\geq 3 - < 5$	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
MEK (METHYL ETHYL KETONE), BUTANONE substance with a Community workplace exposure limit	CAS-No.: 78-93-3 EC-No.: 201-159-0 EC Index-No.: 606-002-00-3 REACH-no: 01-2119457290-43	$\geq 3 - < 5$	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H- and EUH-statements: see section 16

# Bio Ethanol Liquid

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
Self protection of the first-aider	: First aid workers will be equipped with suitable personal protective equipment.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

#### 5.3. Advice for firefighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	---

##### 6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

#### 6.2. Environmental precautions

Avoid release to the environment.

# Bio Ethanol Liquid

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 6.3. Methods and material for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorised site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.
- Packaging materials : Store always product in container of same material as original container.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

<b>ethanol; ethyl alcohol (64-17-5)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Ethanol
WEL TWA (OEL TWA)	1920 mg/m <sup>3</sup>
	1000 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>isopropanol (67-63-0)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Propan-2-ol
WEL TWA (OEL TWA)	999 mg/m <sup>3</sup>
	400 ppm
WEL STEL (OEL STEL)	1250 mg/m <sup>3</sup>
	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

# Bio Ethanol Liquid

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>MEK (METHYL ETHYL KETONE), BUTANONE (78-93-3)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Butan-2-one (methyl ethyl ketone)
WEL TWA (OEL TWA)	600 mg/m <sup>3</sup>
	200 ppm
WEL STEL (OEL STEL)	899 mg/m <sup>3</sup>
	300 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>United Kingdom - Biological limit values</b>	
Local name	Butan-2-one (methyl ethyl ketone)
BMGV	70 µmol/l Parameter: butan-2-one - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

# Bio Ethanol Liquid

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 8.2.2.3. Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 78 °C
Flash point	: 12 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Solubility	: Miscible.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

# Bio Ethanol Liquid

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### ethanol; ethyl alcohol (64-17-5)

LD50 oral rat	15010 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 14450 - 15560
LD50 oral	8300 mg/kg bodyweight Animal: mouse

#### isopropanol (67-63-0)

LD50 oral rat	5840 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	12800 mg/kg Source: ECHA

#### MEK (METHYL ETHYL KETONE), BUTANONE (78-93-3)

LD50 oral rat	2193 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	32 mg/l Source: RTECS

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

#### ethanol; ethyl alcohol (64-17-5)

IARC group	1 - Carcinogenic to humans
------------	----------------------------

#### isopropanol (67-63-0)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified  
STOT-single exposure : Not classified

#### isopropanol (67-63-0)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

#### MEK (METHYL ETHYL KETONE), BUTANONE (78-93-3)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Not classified

#### ethanol; ethyl alcohol (64-17-5)

NOAEL (subchronic, oral, animal/male, 90 days)	< 9700 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (subchronic, oral, animal/female, 90 days)	> 9400 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)

Aspiration hazard : Not classified

#### isopropanol (67-63-0)

Viscosity, kinematic	2.658 mm <sup>2</sup> /s
----------------------	--------------------------

# Bio Ethanol Liquid

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### MEK (METHYL ETHYL KETONE), BUTANONE (78-93-3)

Viscosity, kinematic	0.494 mm <sup>2</sup> /s
----------------------	--------------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

### ethanol; ethyl alcohol (64-17-5)

LC50 - Fish [1]	14.2 g/l Test organisms (species): Pimephales promelas
ErC50 algae	275 mg/l Source: ECHA
NOEC (chronic)	9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'

### isopropanol (67-63-0)

LC50 - Fish [1]	10000 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas

### MEK (METHYL ETHYL KETONE), BUTANONE (78-93-3)

LC50 - Fish [1]	2993 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	308 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	1972 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	2029 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

### 12.2. Persistence and degradability

#### Bio Ethanol Liquid

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### ethanol; ethyl alcohol (64-17-5)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### isopropanol (67-63-0)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### MEK (METHYL ETHYL KETONE), BUTANONE (78-93-3)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

### 12.3. Bioaccumulative potential

#### ethanol; ethyl alcohol (64-17-5)

Partition coefficient n-octanol/water (Log Pow)	-0.32 Source: ICSC
---	--------------------

#### isopropanol (67-63-0)

Partition coefficient n-octanol/water (Log Pow)	0.05 Source: ICSC
---	-------------------

# Bio Ethanol Liquid

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### MEK (METHYL ETHYL KETONE), BUTANONE (78-93-3)

Partition coefficient n-octanol/water (Log Pow) 0.29 Source: ICSC

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

##### Component

isopropanol (67-63-0) This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII  
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

#### 12.6. Other adverse effects

No additional information available






## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Sewage disposal recommendations : Disposal must be done according to official regulations.  
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.  
Additional information : Flammable vapours may accumulate in the container. Do not re-use empty containers.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
UN 1170	UN 1170	UN 1170	UN 1170	UN 1170
<b>14.2. UN proper shipping name</b>				
ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)	Ethyl alcohol solution	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
<b>Transport document description</b>				
UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3, II, (D/E)	UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3, II	UN 1170 Ethyl alcohol solution, 3, II	UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3, II	UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3, II
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
				
<b>14.4. Packing group</b>				
II	II	II	II	II

# Bio Ethanol Liquid

## Safety Data Sheet


according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 144, 601
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: •2YE

#### Transport by sea

Special provisions (IMDG)	: 144
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Colourless, volatile liquids. Pure ETHANOL: flashpoint 13°C c.c. Explosive limits: 3.3% to 19%. Miscible with water.

#### Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3, A58, A180
ERG code (IATA)	: 3L

#### Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 144, 601
Limited quantities (ADN)	: 1 L

# Bio Ethanol Liquid

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Excepted quantities (ADN) : E2  
Equipment required (ADN) : PP, EX, A  
Ventilation (ADN) : VE01  
Number of blue cones/lights (ADN) : 1

### Rail transport

Classification code (RID) : F1  
Special provisions (RID) : 144, 601  
Limited quantities (RID) : 1L  
Excepted quantities (RID) : E2  
Packing instructions (RID) : P001, IBC02, R001  
Mixed packing provisions (RID) : MP19  
Portable tank and bulk container instructions (RID) : T4  
Portable tank and bulk container special provisions (RID) : TP1  
Tank codes for RID tanks (RID) : LGBF  
Transport category (RID) : 2  
Colis express (express parcels) (RID) : CE7  
Hazard identification number (RID) : 33

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

##### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

##### Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

##### Drug Precursors Regulation (EC 273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Methylethylketone	Butanone	78-93-3	2914 12 00	Category 3		Annex I

#### 15.1.2. National regulations

No additional information available

# Bio Ethanol Liquid

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

#### Indication of changes:

New format.

#### Indication of changes

Section	Changed item	Comments
1.1	Additional information	<b>Added</b> UFI
1.3	Additional information	<b>Modified</b>
1.4	Additional information	<b>Added</b>
2.2	Precautionary statements (CLP)	<b>Modified</b>

#### Abbreviations and acronyms:

ACGIH	American Conference of Government Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
CSA	Chemical safety assessment
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
EN	European Standard
EWC	European waste catalogue
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
Log Kow	Partition coefficient n-octanol/water (Log Kow)

# Bio Ethanol Liquid

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>Abbreviations and acronyms:</b>	
Log Pow	Partition coefficient n-octanol/water (Log Pow)
MAK	maximum workplace concentration
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety Health Administration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
PPE	Personal protection equipment
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TF	Technical function
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TWA	Time Weighted Average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
UFI	Unique Formula Identifier

<b>Full text of H- and EUH-statements:</b>	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.